

<image>

www.cnholy.cn



Why Choose Us?

Comprehensive Tool Solutions for the Entire HVAC Pipeline Workflow.

We specialize in covering the full process of HVAC pipeline construction, with four core processes: **Connection, Fixation, Shaping, and Processing:**

- **Connection Tools:** Crimping tools, axial press tools, and pipe expanding tools, compatible with aluminum-plastic pipes, stainless steel pipes, PE-X pipes, etc.
- **Fixation Tools:** Plastic clips and staple gun tacker series, featuring a patented inspection window to resolve on-site issues in 1 second.
- **Shaping Tools:** Pipe benders and straightener supporting 16mm–40mm pipe diameters, ensuring zero deformation.
- **Processing Tools:** Pipe cutters and pipe chamfer tools with integrated blade technology for clean, burr-free cuts, extending pipeline service life.

Intelligent Manufacturing – Double Guarantee of Precision & Efficiency

- Advanced Equipment Cluster: Features 7-axis 5-linkage turning-milling composite machines that enable one-time clamping for precision processing of complex operations (turning, milling, drilling, boring, tapping, engraving) on critical components like cylinders, shortening the process chain and boosting efficiency.
- Flexible Automated Production Line: Achieves fully automated processing from feeding, machining,inspection, to unloading, ensuring production flexibility, minimizing human error, and adapting to diverse market demands.

Core Competitiveness

Customized Service:

Customized products aim to meet unique client needs, including branding, labeling, and packaging design.

Industry Experience:

We serve for global markets with over 10 million tools delivered, participating in large-scale projects worldwide. "We understand tools and their application scenarios."

Service Excellence:

Free Support: Tool selection guidance, construction plan optimization, and video training.

Lifetime Maintenance:

Extended warranty for core components, with 48-hour resolution for quality issues.

Flexible Collaboration:

OEM/ODM customization , from logo engraving to functional module adjustments.

Collaborative Value

By choosing us, you gain:

Construction Efficiency Revolution: High-precision tools reduce rework, shorten the construction period

System Safety Assurance:

Sealing performance is validated by pressure testing, minimizing risk of water leakage.

Cost Optimization:

It will extend tool lifespan and reduce maintenance expenses for lower total operational costs.

Defining a New standard for HVAC Construction with Precision Craftsmanship!

CONTENTS



PIPE CRIMPING TOOL





| Characteristic Types of tools | The service life of a single battery | Maintenance | Transmission mode |
|----------------------------------|--------------------------------------|-------------|--|
| Mechanical type | 5-600 Times | Not need | Insensitive transmission, constant force |
| Hydraulic type | 2-300 Times | 1 Year/time | Hydraulic transmission |

Specifications

| | Stainless steel tube: DN25mm (with a wall thickness of 1.0mm) | Input voltage | AC 100V-240V |
|---------------------------|--|--|----------------------------|
| Application | DN35mm is compatible with universal card clamp and card ring | Battery charging time | approximately 40 minutes |
| specifications | Thin-walled copper tube: DN35mm (wall thickness 1.5mm) | Weight | 2.4kgs (tool with battery) |
| | Aluminum-plastic composite tube: DN40mm | Product size | 400*119*76mm |
| Rated output | 19KN | Weight of tool kit (excluding card clamp) | 4.9kg |
| Rated power | 360W | 18V 2.0Ah lithium battery (single) | 0.3kg |
| Stroke | 30mm | Charger | 0.5kg |
| Single card pressing time | 2-4s | Plastic case | 1.7kg |
| Standard battery | 18V2.0Ah lithium battery | | |

This tool includes two 2.0Ah lithium batteries, one charger, and one dedicated toolbox (compatible with calipers)

PIPE CRIMPING TOOL



| HLTL1110 Manual Crimping Tool The length of handles can be extended to 78cm which can save effort when working. The head can be rotated 360° so it is suitable for various complicated environment. The molds can be replaceable quickly, press the button then the molds can slide freely. Horizontal press: the pressure distribution around the steel sleeve is balanced with the parallel advance of the pressure |
|--|
| Horizontal press: the pressure distribution around the steel sleeve is balanced with the parallel advance of the pressure die, then the crimping effect is better. |

Specifications

| Application Size | Ø1/2", 3/4", 1" Ø12, 14, 16, 18, 20, 22, 25(26), 28, 32mm | Fitting Jaw Type | V / H / TH / M |
|--------------------|--|------------------|----------------|
| Weight of Tool Kit | 5.8kg | Product Size | 610*330*240mm |
| Packaging | Plastic Box | | |



| Application Size | Ø1/2", 3/4", 1" Ø12, 14, 16, 18, 20, 22, 25(26), 28, 32mm | Fitting Jaw Type | U / TH |
|--------------------|--|------------------|---------------|
| Weight of Tool Kit | 3.7kg | Product Size | 510*300*350mm |
| Packaging | Plastic Box | | |

PIPE CRIMPING TOOL





Specifications

| Application Size | Ø12, 14, 16, 18, 20mm | Fitting Jaw Type | U / TH |
|--------------------|-----------------------|------------------|---------------|
| Weight of Tool Kit | 2.4kg | Product Size | 440*300*200mm |
| Packaging | Plastic Box | | |



| 5 | | | | | |
|--|--------------|--|--|--|--|
| Application Size TH: Ø12, 14, 16, 18, 20, 25, 26, 32mm U: Ø14, 16, 18, 20, 25, 26, 32mm H: Ø12, 14, 16, 18, 20, 25, 26 32mm | | | | | |
| Packaging | | | | | |
| Packing Size | Customizable | | | | |

JAW BASE: HLTL1B00 ROUND JAW: HLTL1BX0 Series

- Economic Caliper
- A set of calipers paired with interchangeable, Multi-size & speccomplant jaws, offering high cost-effectiveness.
- Quick jaw replacement achieved with a simple pull-and-push action

PIPE SLIDING TIGHTENING TOOL





Specifications

| Application Specifications | Ø16, 20, 25, 32mm | Standard Battery | 18V*2.0Ah / 18V*4.0Ah / 18V*5.0Ah lithium battery |
|----------------------------|---|------------------|--|
| Pipe | S3.2 Series Aluminium Pipes, S4 Series Pipes Fittings or European Standard Square Teeth Germany Rehau, TECE, Watts style pipes and fittings | Input Voltage | AC 100V-240V |
| Rated Output | 18KN | Weight | 5kg |
| Stroke | 39mm | Packaging | Plastic Box |



| Application Specifications | Ø16, 20, 25, 32mm | Weight | 7.5kg |
|----------------------------|-------------------|----------------|---------------|
| Pipe | S5 series pipes | Packaging | Plastic box |
| Stroke | 38mm | Packaging Size | 515*205*370mm |

PIPE SLIDING TIGHTENING TOOL





Specifications

| Application Specifications | Ø16, 20, 25, 32mm | Weight | 7.5kg |
|----------------------------|---|----------------|---------------|
| • Pipe | S3.2 series Aluminium pipes, S4 series pipes and fittings European standard square teeth Germany Rehau, TECE, Watts style | Packaging | Plastic box |
| | pipes and fittings | Packaging Size | 515*205*370mm |
| Rated Output | 22KN | Stroke | 38mm |



| Application Specifications | Ø16, 20, 25, 32mm | Weight | 8kg |
|----------------------------|---|----------------|---------------|
| Pipe | S3.2 series Aluminium pipes,S4 series pipes and fittings European standard square teeth Germany Rehau,TECE,Watts style pipes and fittings | Packaging | Plastic box |
| Stroke | 40mm | Packaging Size | 515*205*307mm |

PIPE EXPANDER TOOL





Specifications

| Application Specifications | European Standard: Ø16*1.8 / 2.0 / 2.2mm Ø20*1.9 / 2.0 / 2.8mm Ø25*2.3 / 3.5mm Ø32*2.9mm | Standard battery | 18V*2.5Ah 18V*4.0Ah 18V*5.0Ah Lithium battery |
|-------------------------------|---|------------------|--|
| | American Standard: Ø1/2", 3/4", 1" | Weight | 2kg |
| Input voltage | AC 110V-240V | Packaging | Plastic box |



Specifications

| Application Specifications | European Standard: Ø16*1.8 / 2.0 / 2.2mm Ø20*1.9 / 2.0 / 2.8mm Ø25*2.3 / 3.5mm Ø32*2.9mm | Standard battery | 18V*2.5Ah 18V*4.0Ah 18V*5.0Ah Lithium battery |
|-------------------------------|---|------------------|--|
| | American Standard: Ø1/2", 3/4", 1" | Weight | 2kg |
| Input voltage | AC 110V-240V | Packaging | Plastic box |



| Application Specifications | Ø12, 16, 20, 25, 32mm | Pipe | S5 Series |
|----------------------------|-----------------------|--------|-----------|
| Packaging | Plastic box | Weight | 0.5kg |

PIPE BENDER AND STRAIGHTENER



| HLTL3010 Pipe Bender Used for PEX-AL-PEX pipes and copper-plastic pipes |
|--|
| The angle can be bent to more than 90 degrees. Also it can keep the pipe's wall without damage and the shape of pipe no change during bending Die casting aluminum alloy main body and nylon module, make |
| the tool high strength, no fracture and light weight, easy to carry |

Specifications

| Application Specifications | Ø16, 20, 25, 32mm | Packing size | 420*370*325mm |
|----------------------------|-------------------|--------------|---------------|
| Packaging | Plastic box | Weight | 3.4kg |



Specifications

| Application Specifications | Ø16, 20, 25, 32mm | Packing size | 420*370*325mm |
|----------------------------|-------------------|--------------|---------------|
| Packaging | Plastic box | Weight | 3.4kg |



| Application Specifications | Ø16, 20, 25, 32mm | | |
|-------------------------------|-------------------|--|--|
|-------------------------------|-------------------|--|--|

PIPE BENDER AND STRAIGHTENER





Specifications

| Application Specifications | Ø16, 20, 25, 32mm | Packing Size | 235*175*65mm |
|----------------------------|-------------------|--------------|--------------|
| Packaging | Carton | Weight | 4.4kg |



| Application Specifications | Ø16, 20, 25, 32mm | Packing Size | 360*330*245mm |
|----------------------------|-------------------|--------------|---------------|
| Packaging | Carton | Weight | 5.2kg |

STAPLE GUN TACKER





Specifications

| Application Specifications | European standard Ø16, 20mm (Length:4cm & 6cm) | Packaging Size | 770*380*100mm |
|-------------------------------|--|-------------------|---------------|
| Packaging | Carton | Weight | 3.3kg |



HLTL4120

- Plastic Staple Gun Tacker for Underfloor Heating Pipe
- Help installers work in an upright position, reducing physical strain while speeding up installation
- Made of plastic and aluminum alloy, light weight and durable

Specifications

| Application Specifications | European standard Ø16, 20mm (Length:4cm-6cm) | Fackaullu | 770*380*100mm |
|-------------------------------|--|-----------|---------------|
| Packaging | Carton | Weight | 2.3kg |



HLTL4A00

- Plastic Clips for UnderfloorHeating Pipe
- Burr-free
- Good toughness
- Can easily impale the XPS board without puncturing the pipe

Specifications

| Application Specifications | European standard Ø16, 20mm (Length:4cm and 6cm) | Packaging Size | |
|-------------------------------|--|-------------------|----------|
| Packaging | Carton | Weight | 1.2/1.6g |



HLTL4000

- Decoiler Iron material, powder coating on the surfae
- The width and height of the bracket can be sdjusted through three adjustment holes
- Double-bearing design ensures stable rotation, high load capacity, and superior stability

| Scope of adaptation | Heating pipe collection and release | Packaging Size | 800*210*200mm |
|---------------------|---|-------------------|---------------|
| Packaging | Carton | Weight | 11.7kg |

PIPE CHAMFER TOOL

| | HLTL2160 Internal and external full circle chamfering to Suitable for trimming PEX-AL-PEX pipes and design improves productivity The anti-drop cover carefully proteces the bl The stainless steel multi-blade takes into acc chamfering and deburring | d pure plastic pipes,Ma ade from being damag | ed |
|-------------------------------|--|---|-------------------------|
| Specifications | | | |
| Application Specifications | European standard or national standard: Ø16, 20mm | Packing Size | 200*100mm |
| Packaging | Blister box | Weight | 288g |
| T | HLTL2100 4-IN-1 Internal Pipe Chamfer Tool 4-in-1 tool, it's convenient Made of steel, heat treatment, durable After chamfering, the inner of the pipe becor fitting into the pipe will not damage the O-rin | | rrs, then inserting the |
| Specifications | | | |
| Application Specifications | Ø16, 20, 25(26), 32mm (other sizes can be customized) | Packing Size | 200*100mm |
| Packaging | Plastic Box | Weight | 252g |
| | | | |
| Specifications | 4-in-1 tool, convenient Made of steel, heat treatment, durable After chamfering, the inner of the pipe becon fitting into the pipe will not damage the O-ring | nes smooth without bu g | rrs, then inserting the |
| Application Specifications | Ø16, 20, 25(26), 32mm (other sizes can be customized) | Packing Size | 200*100mm |
| Packaging | Plastic Box | Weight | 351g |
| | HLTL2120 Big Size Internal Pipe Chamfer Tool Made of steel, heat treatment, durable After chamfering, the inner of the pipe becor fitting into the pipe will not damage the O-rin | | rrs, then inserting the |
| Specifications | | | |
| Application Specifications | Ø40, 50, 63mm | Packing Size | 200*100mm |
| Packaging | Plastic Box | Weight | 351g |
| | HLTL2130 3-IN-1 Internal Pipe Chamfer Tool It's made of plastic, light weight It can used for both internal and external of p | pipe | |
| Specifications | 1 | | |
| Application Specifications | Ø10-12-16mm Ø16-18-20mm Ø16-25-32mm Ø16-20-32mm Ø16-20-25/26mm Ø20-25-32mm | Packing Size | |
| Packaging | Carton | Weight | 100g |
| i ackaging | Calton | Weight | 1009 |

Hsly

PIPE CUTTER



| J • • | HLTL220 | D | |
|--------------|-----------------------|---------------------|--|
| | Product Name | Plastic Pipe Cutter | |
| | Application Size | Ø16~25mm | |
| | Handle's Materials | Plastic | |
| | Pipe | PEX / PVC / PPR | |



| HLTL2250 | | |
|-----------------------|---------------------------------|--|
| Product Name | Pipe Cutter | |
| Application Size | Ø16~32mm | |
| Handle's Materials | Aluminum Alloy | |
| Pipe | PEX / PVC / PPR / PEX-AL-PEX | |

| | HLTL226 | 60 | | |
|--|-----------------------|---------------------------------|--|--|
| | Product Name | Pipe Cutter | | |
| | Application Size | Ø16~32mm | | |
| | Handle's Materials | Aluminum Alloy | | |
| | Pipe | PEX / PVC / PPR / PEX-AL-PEX | | |

| | HLTL227 | 0 | |
|--|-----------------------|---------------------------------|--|
| | Product Name | Pipe Cutter | |
| | Application Size | Ø16~64mm | |
| | Handle's Materials | Aluminum Alloy | |
| | Pipe | PEX / PVC / PPR / PEX-AL-PEX | |



| C | HLTL2290 | |
|---|-----------------------|---|
| | Product Name | Pipe Cutter |
| | Application Size | Ø16~25mm |
| | Handle's Materials | Plastic |
| | Pipe | Copper Pipe / Plastic Pipe SS Pipe / Al Pipe / Bellows |

| | HLTL2210 | |
|--|-----------------------|---------------------------------|
| | Product Name | Pipe Cutter |
| | Application Size | Ø16~32mm |
| | Handle's Materials | Aluminum Alloy |
| | Pipe | PEX / PVC / PPR / PEX-AL-PEX |

| | HLTL222 |) | |
|--|-----------------------|---------------------------------|--|
| | Product Name | Pipe Cutter | |
| | Application Size | Ø16~32mm | |
| | Handle's Materials | Aluminum Alloy | |
| | Pipe | PEX / PVC / PPR / PEX-AL-PEX | |

| | HLTL2230 | |
|--|-----------------------|---------------------------------|
| | Product Name | Plastic Pipe Cutter |
| | Application Size | Ø16~32mm |
| | Handle's Materials | Aluminum Alloy |
| | Pipe | PEX / PVC / PPR / PEX-AL-PEX |

| | HLTL224 | 0 | |
|--|-----------------------|---------------------------------|--|
| | Product Name | Pipe Cutter | |
| | Application Size | Ø16~32mm | |
| | Handle's Materials | Aluminum Alloy | |
| | Pipe | PEX / PVC / PPR / PEX-AL-PEX | |

OTHER PRODUCTS

| HLTL5100 |
|--|
| Pipe Caliper Gauge |
| It's used to verify that the pipe installation meets the requirements |
| Insert it into the joint of the corresponding-sized pipe connection. Successful engagement indicates proper installation; otherwise, it fails the test |

l ş l

| Application Size Ø16, 20, 25, 32mm | Packaging | Carton |
|--|-----------|--------|
|--|-----------|--------|

| Note that the second seco | HLTL5000 • Hydraulic Test Pump |
|--|--|
| | It's used to check the quality of the installationApply pressure to check if the connected pipe is leaking" |





NINGBO HOLY HVAC CO., LTD

Add:No.485 Zhengtong Road, Kandun Street Cixi,Ningbo,P.R.China Tel:+86(0)574 63035806 63286656 E-mail:hu@cnholy.cn mark@cnholy.cn Http: //www.cnholy.cn